

Product Description:

IB Clad Termination Bar is fabricated from 24 gauge, ASTM A653-09, CS Type B, G90 galvanized sheet metal with a durable 45-mil non-reinforced IB PVC film with acrylic finish laminated to the top surface. Bars are 2" wide with a hemmed caulk lip on the top and a hemmed bottom edge and can be installed over membrane flashings at vertical surfaces (like a traditional termination bar) or installed first to allow for the membrane to be welded directly to the IB Clad Termination Bar for a cleaner application.

Sizes:

2" wide x 10' long

Colors:

White, Bronze, Tan, and Gray



Also available in 24-gauge Clad SAE 304 stainless steel (White only)



Packaging:

IB Clad Termination Bar are sold individually in 10-foot pieces and are shipped in a 10' cardboard box. Max 50 units per tube.

Weight:

- 3.0 lbs. per piece; 150 lbs. per 50-unit tube

Features:

- Durable 45-mil IB PVC non-reinforced film laminated to corrosion resistant 24-gauge, G90 galvanized metal
- Acrylic finish top surface
- Installed either on top or underneath the roofing membrane

Installation:

Refer to IB Specifications and Construction Details for additional installation requirements. Secure termination bar to the wall with approved IB Fasteners suitable for the substrate spaced no more than 6" o.c. for most applications.

Note: Maximum warranty term limited to twenty (20) years when used to terminate flashing without a metal counter flashing.

Front



Back



Product details stated are nominal as manufactured, and the results of tests and/or calculations and therefore are non-binding and do not represent a guarantee or warranted characteristics. User and/or designer are responsible for confirming suitable performance for specific application and conforming with all applicable laws and regulations.