Technical Data Sheet

IB® Pitch Pan

IB Roof Systems®

Product Description:

IB Pitch Pans are fabricated from IB PVC Clad Metal constructed with a durable 45 mil non-reinforced IB PVC film laminated to 24 gauge, G90 coated galvanized sheet metal. Pitch pans are custom fabricated to your exact specification. A factory welded; reinforced IB PVC Single-Ply target flashing is bonded to the clad which allows for easy application over the newly installed IB roof system. They are intended to be used in conjunction with M-1 Sealant and One-Part Pourable Penetration Sealant.

Packaging:

Sold as individual units.

Features:

- · Split pan format for ease of installation
- · Factory welded reinforced membrane target
- Integral flanges for securement
- Custom orders available for a variety of membrane thicknesses and color options


Available Membrane Colors:



Attachment:

Refer to IB Specifications and Construction Details for installation requirements and additional information for approved substrates and specific uses. IB Pitch Pans are intended to be used in conjunction with M-1 Sealant (sold separately) and One-Part Pourable Penetration Sealant (sold separately). IB Pitch Pans must be secured in place over the installed IB membrane with IB Fasteners approved for the substrate type. Split pan seams must be sealed with a continuous bead of M-1 Sealant and closed with a poprivets spaced approximately 1" o.c. (not supplied).





Product details stated are nominal as manufactured, and the results of tests and/or calculations and therefore are non-binding and do not represent a guarantee or warranted characteristics. User and/or designer are responsible for confirming suitable performance for specific application and conforming with all applicable laws and regulations.