

Product Description:

IB Snap Fascia is a two-piece assembly with a raised rigid retainer/clip base plate and a raised decorative, snap on facing cover designed for terminating IB PVC membrane systems at the perimeter edges, or for vertically terminating IB PVC base flashing. The IB Snap Facing system comes standard with 24 ga. Kynar 500 coated galvanized steel decorative snap on facing and a 0.063 aluminum retainer/clip base plate with 9/32" pre punched holes for fastening 12" on center in 10.0' standard lengths.

Features:

- Kynar 500 coated 24 ga. Kynar 500 coated galvanized steel
- 0.063 aluminum retainer/clip base plate
- Installed on top of the roofing membrane
- Can be used as a surface mounted counter flashing vertical base flashing applications.
- Design allows for a dual sealant termination by providing a continuous positive pressure compression of the membrane to the underlying structure.

Sizes:

Standard face size is 2-1/4" wide x 10' long
Custom face sizes are special order up to 8-1/2" wide x 10' long.

Special Order Materials & Finishes:

- 0.032", 0.040", and 0.050" Aluminum
- 22 ga. and 24 ga. Stainless Steel
- Mill Finish
- Prefinished Anodized

Colors:

Standard stock colors for 2-1/4" face are White, Bronze, Tan, and Gray



Also available in special order colors below

Concord Cream	Redwood	Siam Blue	Medium Bronze
Sandstone	Mission Red	Black	Rawhide
Chocolate Brown	Ascot White	Forest Green	Patina Green
Charcoal Gray	Regal Blue	Turquoise	Shale Gray
Slate Blue	Hartford Green	Boysenberry	Hemlock Green
Bright Red	Coppertone	Antique Patina	Silversmith
Champagne	Titanium		

Packaging:

IB Snap Fascia are sold individually in 10-foot pieces and are shipped in a 10' cardboard box. Max 50 units per box.

Front



Back



Product details stated are nominal as manufactured, and the results of tests and/or calculations and therefore are non-binding and do not represent a guarantee or warranted characteristics. User and/or designer are responsible for confirming suitable performance for specific application and conforming with all applicable laws and regulations

Installation:

Refer to IB Specifications and Construction Details for additional installation requirements. Ensure that roofing membrane is continued up the side wall far enough to be covered by the raised rigid retainer/clip base plate. Position the raised rigid retainer/clip base plate as shown in the detail drawings. Attach using the mechanical fasteners (by installer). Locate fasteners in each pre-punched hole. Space each 10'-0" section by 1/8" (or 1/4" in cold weather) to allow for thermal expansion. Position the snap on facing cover as shown in the detail drawings (parallel to the raised rigid retainer/clip base plate). Hook the bottom of the snap on facing cover on the bottom lip of the raised rigid retainer/clip base plate and push the top of the snap on facing cover until it snaps it into position. Lap each adjoining piece of IB Snap Fascia Assembly a min. of 1" to allow for thermal expansion. Stagger all fascia cover seams so that they do not align with raised rigid retainer/clip base plate seams. Apply a continuous (3/8") wide bead of sealant to the top side of the IB Snap Fascia (see detail drawing). Field bevel cut raised rigid retainer/clip base plate and IB Snap Fascia for appropriate corner.