



	<u>_</u>	16 PER	R 4' X 4'		,					32 PEF	R 4' X 8'			
6" 12"	0	0	0	0		6" 12"	0	0	0	0	0	⊙	0	0
+	1	0	0	0		+	0	0	0	0	0	0	0	0
FIELD 12" (1 PER 1.00 SQ FT)	0	⊙	0	0		12"	•	0	0	•	•	⊙	0	0
12" _ 6"	0	0	0	0		12" <u>+</u> 6"	0	0	0	0	0	0	0	0
_	6"	12"-+-1	2" -+- 1	2"→ 6"	ĺ		6" 1	2"-+-1	2" - - 12			2" -+- 12	2"-+-1	2" 6"
		20 PER	R 4' X 4'			1	6" - 1	2" - - 1	2"		₹ 4' X 8' 2"	2")" - - 1	2"→ 6"
<u>6"</u>	0	0	0	①	12"	6" 6"	0	·	·	<u> </u>	<u> </u>	0	0	·
12"		0	(9	+	6"	(Ð	0		(9	(9
PERIMETER	0		9	0	12" 1	1	0	0	0	0	0	0	0	0
(ENHANCEMENT) 1	0) ())	0	12"	12"	0	0	0	0	0	0	0	0
12"		0	(9	<u>.</u>	6"	(9	((9	(9
12" _ 6"	0	\odot	\odot	\odot	×	6"	0	\odot	0	o	0	0	0	⊙
_	6" 6'	" 6" 6"	6" 6"	6" 6"	İ	:	 12" -	- 2	4" -		4" 	 - 2	4"	12"
		22 PER	R 4' X 4'			ı	6" 1:	2"1	2" - - 12	400	R 4' X 8' 2" - - 1:	2" 12	2" 1	2" 6"
6" †	0	· ·	0	0	12"	6"	0	0	0	0	0	0	0	0
CORNER 12"	A5000000	⊙ ⁻		9	1	6"	(Ð	(9	(A 107/0
(ENHANCEMENT)	0	\odot	0	\odot	12"	6"	0	0	0	\odot	0	\odot	0	0
12"	25,50	⊙		9	+	6"	(Ð	((Ð	(0
<u> </u>	0	•	0	0	12"	535 355	0	0	•	0	0	0	0	⊙
12" _ 6"	1000	0		<u> </u>	<u> </u>	6" 6"		Ð _	0			9 	0	20000
	0	<u> </u>	0	<u> </u>			0	0	0	0	0	0	0	0
~ "	6" 6'	" 6" - 1	2" 6"	6" 6"		ŀ	 12" 	2	4" — -	 2	4" 	2	4"	 12"- -

NOTES:

- 1. FASTENING PATTERNS ARE PROVIDED AS GUIDELINES FOR FASTENER PLACEMENT FOR MECHANICALLY ATTACHED INSULATION OR COVER BOARD UNDER A FULLY ADHERED MEMBRANE SYSTEM.
- 2. AN APPROVED COVER BOARD IS REQUIRED FOR EPS, XPS, & POLYISOCYANURATE INSULATIONS NOT APPROVED BY IB ROOF SYSTEMS.
- 3. REFER TO TABLE A 2 FOR MINIMUM REQUIREMENTS FOR INSULATION FASTNENING SCHEDULE FOR ADHERED IB ROOF MEMBRANES

Scale:	Detail Name:		Detail Number:
NTS	1 Per 1 Fastening Patterns fo	FA-AT-12	
Submitte	ed By:	Project:	
Address:		Address:	
Telepho	one:		