



| | | Fully . | Adhered Membrane (SP) - Exis | sting Roof | (MB) - Wood Deck | (Recover) | | |
|--|---|---|---|--|---|--|-------------------------------------|--|
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | IB FLEECEBACK MEMBRANE | | | |
| | | | | | | | | |
| | | | | | | APPROVED LOW RISE MEMBRANE ADHESIVE - | | |
| | | | | / | / SP | | | |
| | | | | | | | | |
| | | | | <i></i> | | – EXISTING ROOF* MODIFIED BITUMEN | | |
| + | + - | - + + | + + + + | + ++ | - + <u>/</u> - | DUILIED BITOMEN | | |
| | , | , | , , | | | | | |
| | | | | | W(| OOD DECK | | |
| | | | | | | | | |
| | | • | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | e Rating / x. Slope¹ Deck Type | | IB Fleeceback Membrane (over Exi Existing Roof | | isting Modified Bitumen Roof) Attachment | | Max. Design Pressure** | |
| | □ Not | | Existing Modified Bitumen Roof | | CR-20 Spatter Pattern 3.75 lbs/square | | Minimum Req. | |
| | Rated 7/16 OSB | | | | | | for IB Warranty Minimum Reg. | |
| | ¹ Not Rated | 1/2" Plywood | Existing Modified Bitumen Roof | | | CR-20 Spatter Pattern 3.75 lbs/square | | |
| | Not 19/32" Plywood Existing APP Granulated Modified Bit | | ımen Roof | CR-20 Spatter Pattern | | for IB Warranty -75.0 psf | | |
| Ļ | Rated | | Existing 74 1 Grandiated Medined Endiner 17601 | | 3.75 lbs/square | | (class 150) -112.5 psf | |
| ľ | Not Rated 19/32" Plywood Existing | | Existing APP Granulated Modified Bitu | kisting APP Granulated Modified Bitumen Roof | | CR-20 Spatter Pattern 3.75 lbs/square | | |
| | | SBS modified bitumen, smooth e(s): 1This assembly is not UL | | | | | | |
| ** R | Refer to Substrate F | Resistance table for required | | ne inetallation | n details annrovals and lim | itations for the above a | ssamhlias nlassa rafar | |
| | | | ms Specifications Manual. For Technical | Services plea | se contact us at 800-426-10 | 526. | - | |
| N | lembranes: | | Membrane Color: | Wa | arranty Length*** | Warran | ty Type*** | |
| ☐ IB PVC Single-Ply FB 50 Mil ☐ White* | | | | | 15 Year 20 Year | — I — | | |
| | B PVC Single-Ply FE | 3 60 Mil White* | | 15 Year | 20 Year 25 Year | Warranty Plus (WP) | laterial Warranty (CLMW) | |
| | B PVC Single-Ply FE | 3 80 Mil White* | | 15 Year | 20 Year 25 Year | Residential Limited Ma | | |
| * Me | eets CRRC, Title-24 | , & EnergyStar Standards | | | /arranty Selection Guide for Warrant | y Riders, Term Length Limitation | ns, and eligibility requirements of | |
| Sul | bmitted By | <i>r</i> : | | Project | | | | |
| Add | ress: | | | Address | | | | |
| Ema | | | | <u></u> | - ~· | | | |
| | SLASS/F | Ŷ ⟨FM ⟩ | > ES MIAMI DAD | DE COUNT | CRRC | energy ? | | |
| | r(VI | /// > | I I I DAL | DE COUNTY | RATED PRODUCT 0640 | -emy JW | 7/ /4 L | |