



**DECKSHIELD™**

Premium Vinyl Decking Membrane



### DESIGN

DeckShield™ is specifically designed for residential and commercial exterior walkways, patios, decks, balconies, stairways, around swimming pools, hot tubs, and locker rooms. DeckShield™ is designed as a walkable vinyl deck. DeckShield™ must be fully adhered to a properly prepared substrate with approved membrane adhesive.

### FEATURES

- Enhances the Appearance of Decks
- Eliminates Painting and Staining
- Slip Resistant
- Textured Surface

### THE MATERIAL

IB DeckShield™ is a dual-ply embossed and printed vinyl sheet that is laminated to a non-woven polyester fleece backing. The PVC is a calendered film construction and meets the physical performance values of ASTM D4434, Type II.

### AVAILABLE COLORS

DeckShield™ designer colors are available in 4 stunning colors and textures:



Pebblestone



Cobblestone



Royal Oak



Silver Maple

### MAINTENANCE

DeckShield™ cleans easily with soap and water. When cleaned properly, DeckShield™ membrane will continue to perform and look great for many years.

### WARRANTY

DeckShield™ offers up to a 10-year limited warranty against manufacturer's defects. Please refer to the DeckShield™ sample warranty for more details.

### APPROVALS

IB DeckShield™ meets AC-39 for walking decks, AC-75 for roof coverings and is listed with Intertek Code Compliance Research Report CCRR-0395.



### INSTALLATION

IB DeckShield™ is hot-air welded using the Automatic Hot Air Welding Machine or Hot Air Hand Welder to create a clean, durable seam.

### LIMITATIONS

The product is limited for use in areas that are subject to traffic loads generated by residential occupancies only (light pedestrian traffic). Any physical or chemical damage to the membrane must be repaired in accordance with the manufacturer's instructions. The product must not be installed with butt seam joints. Joints must be shingle-lapped in order to shed water.

