



	Fully Adhered Membra	ne (SP) - Existir	ng Roof (MB) - C	Concrete Dec	ck (Recover)	
			_	IB FLEECEBA	CK MEMBRANE	
				APPROVED L	OW RISE	
				MEMBRANE A SPATTER PA	ADHESIVE -	
		./				
<i>                                     </i>	# + + +	<i></i>	<u>                                     </u>	EXISTING RO MODIFIED BIT	OF* TUMEN	
	, , , , , , , , , , , , , , , , , , ,			MODII IED DI	OMEN	
	<b>∀</b> :	Δ	ΔΔ			
	∢ .	✓		STRUCTURAL	CONCRETE	
	Λ Δ					
	Δ	· · · · · · · · · · · · · · · · · · ·	. A			
	✓	4	√			
			<u>.</u>			
Fire Rating /	Deck Type	IB Fleeceback Memi	orane (over Existing N	Modified Bitumen	Roof)	Max. Design
Max. Slope	Structural		Attachment CR-20 Spatter Patter	rn		Pressure** -250 psf
<sup>1</sup> Not Rated	Concrete		3.75 lbs/square			(Class 500)
Fire Classification Note(s): 1This	ified bitumen, smooth or granule surfaced roof on sassembly is not UL Classified.  The contract of the contrac	only.				
For additional information	on about IB Roof Systems requirence IB Roof Systems Specifications					semblies, please refer
Membranes:	Membrane Co		Warranty L			y Type***
IB PVC Single-Ply FB 50 Mil	White*		10 Year 15 Year	20 Year	Total System - No Dolla	-
IB PVC Single-Ply FB 60 Mil	White*		15 Year 20 Year	25 Year	Warranty Plus (WP)	terial Warranty (CLMW)
IB PVC Single-Ply FB 80 Mil	White*		15 Year 20 Year	25 Year	Commercial Limited Mat	
* Meets CRRC, Title-24, & Energ	yStar Standards		***Refer to Warranty Selector the Warranty Program	ction Guide for Warranty R	iders, Term Length Limitations	, and eligibility requirements of
Submitted By:			Project Name:			
Address: Email:			Address:			
CLASSIFIED	⟨FM⟩ FC			CRRC	a ma	
CUL)US	APPROVED ESR-2852	APPR	DVED OVED	RATED PRODUCT 0640	ENERGY STAR	COMPLIANT