



Fully Adhered Membrane (SP) - Existing Roof (SA) - Gypsum Deck (Recover)	
	IB FLEECEBACK MEMBRANE
	APPROVED LOW RISE MEMBRANE ADHESIVE - SPATTER PATTERN
<u> </u>	EXISTING ROOF* SMOOTH ASPHALTIC
	GYPSUM DECK
	r Existing Smooth Asphaltic Roof) chment Max. Design Pressure**
CR-20 Spa	atter Pattern -112.5 psf (Class 225)
Existing Roof: Smooth or granule surfaced asphaltic built-up roof only. Fire Classification Note(s): ¹ UL Class A up to 1":12" limited to any Class A,B, or C built up roof system. ² The use of other IB Approved adhesives may not retain UL Classification. ³ Recover over madified bitumen may not retain fire classification ** Refer to Substrate Resistance table for required pull-out values. For additional information about IB Roof Systems requirements, recommendations, installation details, approvals and limitations for the above assemblies, please refer to the latest edition of the IB Roof Systems Specifications Manual. For Technical Services please contact us at 800-426-1626.	
Membranes: Membrane Color:	Warranty Length*** Warranty Type***
IB PVC Single-Ply FB 50 Mil White*	10 Year 15 Year 20 Year Total System - No Dollar Limit (NDL)
IB PVC Single-Ply FB 60 Mil White*	15 Year 20 Year 25 Year Warranty Plus (WP) Commercial Limited Material Warranty (CLMW)
☐ IB PVC Single-Ply FB 80 Mil ☐ White*	15 Year 20 Year 25 Year Residential Limited Material Warranty (RLMW)
* Meets CRRC, Title-24, & EnergyStar Standards	****Refer to Warranty Selection Guide for Warranty Riders, Term Length Limitations, and eligibility requirements of the Warranty Program
Submitted By: Address: Email:	Project Name: Address:
CULUS APPROVED ESR-2852 MIAMI DADI APPROVED	ECOUNTY RATED PRODUCT OG40 ENERGY STAR