



| Fully Adhered Membrane - Lightweight Insulating Concrete - Concrete Deck (New) | |
|---|--|
| | - IB MEMBRANE |
| | - IB APPROVED ADHESIVE |
| | |
| | $\Delta = \Delta$ $\Delta = \Delta$ STRUCTURAL CONCRETE |
| | |
| Fire Rating / Deck Type | IB Membrane Attachment Max. Design Pressure** |
| LightweightConcrete / Structural Unlimited Concrete | IB Approved Adhesive -242.5 psf (Class 485) |
| Approved Lightweight Concrete: Celcore = Min. 200 psi, min. 2" thick Celcore Cellular Concrete over Structural Concrete, Elastizell = Min 200 psi, min 2" thick Elastizell Lightweight Insulating Concrete over Structural Concrete, Mearlcrete = Min 200 psi, min. 2" thick Mearlcrete over Structural Concrete Fire Classification Note(s): ¹ UL Class A up to 1/2":12" when membrane is adhered with IB Waterborne or IB WaterBorne 636 Adhesive. ** Refer to Substrate Resistance table for required pull-out values. | |
| For additional information about IB Roof Systems requirements, recommendation to the latest edition of the IB Roof Systems Specifications Manual. For Technical S | s, installation details, approvals and limitations for the above assemblies, please refer ervices please contact us at 800-426-1626. |
| Membranes: Membrane Color: | Warranty Length*** Warranty Type*** |
| IB PVC Single-Ply 50 Mil White* Gray Tan Bronze ChemGuard* IB PVC Single-Ply 60 Mil White* Cool Sand* Cool Stone* Gray Tan | 10 Year 15 Year 20 Year 15 Year 20 Year Total System - No Dollar Limit (NDL) Warranty Plus (WP) Commercial Limited Material Warranty (CLMW) |
| IB PVC Single-Ply 80 Mil White* Gray Tan Bronze ChemGuard* * Meets CRRC, Title-24, & EnergyStar Standards | 15 Year 25 Year Residential Limited Material Warranty (RLMW) *** Refer to Warranty Selection Guide for Warranty Riders, Term Length Limitations, and eligibility requirements of |
| Submitted By: Address: Email: | the Warranty Program Project Name: Address: |
| CONSTRUCTION APPROVED | ECOUNTY OVED RATED PROUCT 0640 |