



Fully Adhered Membrane (SP) - Existing Roof (MB) - Steel Deck (<i>Rec</i> over)						
			/	IB FLEECEBACK MEMBRANE		
l						
				APPROVED LOW RISE MEMBRANE ADHESIVE - SPATTER PATTERN		
l			/ /			
l		/				
	//////////////////////////////////////	<u>/////////////////////////////////////</u>	<u>/////////////////////////////////////</u>	EXISTING ROOF* MO	DIFIED BITUME	N
–		- + T	+ _			
				STEEL DECK		
	\mathbb{N}			-		
l	<u> </u>	/				
	e Rating /	Deck Type	IB Fleeceback M	embrane (over Existing Modified	Bitumen Roof)	Max. Design
Ma	ax. Slope			Attachment CR20 Spatter Pattern		Pressure** -257.5 psf
	¹ Not Rated	Min. 22 ga. Type B, Grade 33 Steel	3.75 lbs/square			(Class 515)
	¹ Not Rated	Min. 22 ga. Type B, Grade 33 Steel				-262.5 psf (Class 525)
Existing Roof: APP or SBS modified bitumen, smooth or granule surfaced roof only. Fire Classification Note(s): ¹ This assembly is not UL Classified.						
Fire Classification Note(s): This assembly is not OL Classified. ** Refer to Substrate Resistance table for required pull-out values. For additional information about IB Roof Systems requirements, recommendations, installation details, approvals and limitations for the above assemblies, please refer						
to t	he latest editio	n of the IB Roof Systems Specifications Manu	al. For Technical Ser	vices please contact us at 800-426	-1626.	-
	Membranes:			Warranty Length***		/arranty Type***
	PVC Single-Ply FB		10 Year 15 Year 20 Year Total Syste			n - No Dollar Limit (NDL) ıs (WP)
IB PVC Single-Ply FB 60 Mil				15 Year 20 Year 25 Year Commercial L		
Ib PVC Single-Ply FB 80 Mil White* Ib Year Ib Year						
* Meets CRRC, Title-24, & EnergyStar Standards *** Refer to Warranty Selection Guide for Warranty Riders, Term Length Limitations, and eligibility requirements of the Warranty Program						
	omitted By			Project Name:		
Address: Email:				Address:		
			MIAMI DADE APPROV		ENERGY STAR	COMPLIANT