



Fully Adhered Membrane (SP) - Existing Roof (SA) - Steel Deck (Recover)					
IB FLEECEBACK MEMBRANE					
			APPROVED LOW RISE MEMBRANE ADHESIVE - SPATTER PATTERN		
			EXISTING ROOF* SMOOTH ASPHALTIC		
			STEEL DECK		
Fire Rating / Max. Slope	Deck Type	Deck Type IB Fleeceback Membrane (ov			Max. Design Pressure**
	Min. 22 ga. Type B, Grade 33 Steel	Attachment CR20 Spatter Pattern 3.75 lbs/square			Minimum Req for IB Warranty
1":12"	Min. 22 ga. Type B, Grade 33 Steel	CR20 Spatter Pattern 3.75 lbs/square			-112.5 psf (Class 225)
Existing Roof: Smooth or granule surfaced asphaltic built-up roof only. Fire Classification Note(s): ¹ UL Class A up to 1°:12° limited to any Class A, B or C built up roof system. 2The use of other IB Approved adhesives may not retain UL Classification. 3Recover over modified bitumen may not retain fire classification. classification. ** Refer to Substrate Resistance table for required pull-out values.					
For additional information about IB Roof Systems requirements, recommendations, installation details, approvals and limitations for the above assemblies, please refer to the latest edition of the IB Roof Systems Specifications Manual. For Technical Services please contact us at 800-426-1626.					
Membranes:	Membrane Color:	: Wa	rranty Length***	\ \	Narranty Type***
IB PVC Single-Ply FB 50 Mil		10 Year		Total Syste	em - No Dollar Limit (NDL) Plus (WP)
IB PVC Single-Ply FB 60 Mil White*				al Limited Material Warranty (CLMW)	
* Meets CRRC, Title-24, & EnergyStar Standards *** Refer to Warranty Selection Guide for Warranty Riders, Term Length Limitations, and eligibility requirements of					
Submitted By: Project Name: Address: Address: Email: Address:					
CULL R15546	APPROVED	MIAMI DADE COUNTY APPROVED	RATED PROJUCT 0640	Energy STAR	