


Fully Adhered Membrane - High Strength Cover Board (MA) - Insulation - Existing Roof - Steel Deck (Recover)



Fire Rating / Max. Slope	Deck Type	High Strength Cover Board (over Existing Roof)			IB Membrane Attachment	Max. Design Pressure**
		Type	Attachment	Fasteners		
<input type="checkbox"/> Class 'A' 2" : 12"	Min. 22 ga., Type B, Grade 33 Steel	1/2" AC Foam HS Cover Board	Field: 8 per 4' x 8' (1 per 4 sq. ft.)	IB HD #14 Fastener, IB 3" Insulation Plate	IB Waterborne or IB Vertibond Adhesive	-30.0 psf (Class 60)
<input type="checkbox"/> Class 'A' 2" : 12"	Min. 22 ga., Type B, Grade 33 Steel	1/2" AC Foam HS Cover Board	Field: 14 per 4' x 8' (1 per 2.3 sq. ft.)	IB HD #14 Fastener, IB 3" Insulation Plate	IB Waterborne or IB Vertibond Adhesive	-45.0 psf (Class 90)
<input type="checkbox"/> Class 'A' 2" : 12"	Min. 22 ga., Type B, Grade 80 Steel	1/2" AC Foam HS Cover Board	Field: 24 per 4' x 8' (1 per 1.33 sq. ft.)	IB HD #14 Fastener, IB 3" Insulation Plate	IB Waterborne or IB Vertibond Adhesive	-75.0 psf (Class 150)
<input type="checkbox"/> Class 'A' 2" : 12"	Min. 22 ga., Type B, Grade 80 Steel	1/2" AC Foam HS Cover Board	Field: 32 per 4' x 8' (1 per 1 sq. ft.)	IB HD #14 Fastener, IB 3" Insulation Plate	IB Waterborne or IB Vertibond Adhesive	-105.0 psf (Class 210)

* Existing Roof: SBS or APP modified, or oxidized asphalt smooth coated, mineral surfaced, or gravel surfaced fire rated roofing system.

** Refer to Substrate Resistance table for required pull-out values.

For additional information about IB Roof Systems requirements, recommendations, installation details, approvals and limitations for the above assemblies, please refer to the latest edition of the IB Roof Systems Specifications Manual. For Technical Services please contact us at 800-426-1626.

Membranes:	Colors:	Warranties:	Warranty Lengths:
<input type="checkbox"/> 50 Mil Membrane	<input type="checkbox"/> White* <input type="checkbox"/> Cool Sand* <input type="checkbox"/> ChemGuard*	<input type="checkbox"/> Total System (NDL)	<input type="checkbox"/> 10 yr (50, 60, and 80 mil)
<input type="checkbox"/> 60 Mil Membrane	<input type="checkbox"/> Gray <input type="checkbox"/> Green <input type="checkbox"/> Red	<input type="checkbox"/> Warranty Plus	<input type="checkbox"/> 15 yr (50, 60, and 80 mil)
<input type="checkbox"/> 80 Mil Membrane	<input type="checkbox"/> Tan <input type="checkbox"/> Brown <input type="checkbox"/> Custom: _____	<input type="checkbox"/> Commercial Limited Material	<input type="checkbox"/> 20 yr (60 and 80 mil)
	* Meets CRRC, Title-24, & EnergyStar Standards	<input type="checkbox"/> Lifetime Residential Limited Material	<input type="checkbox"/> 25 yr (80 mil)

Submitted By:

Address:
Telephone:

Project Name:

Address:

