

Elastocol Stick

Product Description:

Elastocol Stick is a fast drying primer consisting of a proprietary blend of SBS polymer, resins and volatile solvents designed to enhance Soprapav'r Vapor Retarder adhesion to a variety of approved substrates. Elastocol Stick contains a maximum VOC content of 500 g/l.

Packaging:

Elastocol Stick is available in five (5) gallon pails

Installation:

Apply to dry, compatible substrates using a brush, roller or spray equipment in a uniform application with full coverage. Coverage rates vary depending upon substrate and surface conditions. Apply Elastocol Stick at a rate of 0.66 to 1.0 gallon per 100 square feet. Elastocol Stick drying time is affected by the application rate, substrate and environment conditions such as temperature, wind, cloud cover and shade. The applicator is responsible for monitoring varying environmental conditions during storage, handling and the application to ensure conditions remain satisfactory. Refer to IB installation instructions for more application information.

Storage & Handling:

Elastocol Stick is high flammable. Store containers away from excessive heat and open flames. Take necessary precautions when handling to prevent rupturing the containers, or breaking the sealed lids prior to use. Containers should be stored on end in a dry, protected storage area away from direct sunlight, to comply with site storage and handling requirements.

Approvals:

Underwriters Laboratories, FM Approvals, ICC/ES, Miami-Dade County and Florida Building Code Product Approvals

