

Millennium Universal Primer

Product Description:

Millennium Universal Primer is an all-purpose water-based primer designed for use with IB Rapid Set Insulation Adhesive, PG-1 insulation and membrane adhesives, and the entire Millennium family of products. The primer is easy to apply and requires no mixing. A red tint offers easy recognition of areas of applied primer.

Packaging:

3.5 gallon pails
36 pails per pallet

Features:

- Easy to apply one-part formulation
- Water based, VOC free
- Quick application, applies in one coat

Color:

Red Tint

Installations:

All work surfaces should be clean, dry, free of dirt, dust, debris, oils, loose gravel, un-adhered coatings, deteriorated membrane and other contaminants that may result in a surface that is not sound. Brush, spray, or roll Millennium Universal Primer in one coat over the entire prepared surface. Coverage rates vary depending upon substrate and surface conditions. Apply Millennium Universal Primer at the approximate rate of 150-250 sq. ft. per gallon and allow to completely dry. Remove all heavy or puddled areas to ensure thorough drying. Drying time will vary based on temperature and relative humidity. Millennium Universal Primer is used to enhance adhesion over existing granule surfaced, prepared aggregate surfaced (gravel removed), and weathered (crazed/oxidized) asphaltic membrane surfaces. Contact IB Technical Services for additional information and limitations on substrates such as glazed asphalt or smooth APP or coated membranes. Refer to IB installation instructions for additional information.

Coverage:

Approximate rate of 150-250 sq. ft. per gallon

Storage & Handling:

Millennium Universal Primer can be stored at room temperature where it will have a shelf life of one year. Keep from freezing.

