

Solar Seal 900 Caulking

Product Description:

Solar Seal 900 Caulking is a multi-purpose polymeric-terpolymer, exterior grade caulking which is compatible with any of IB Roof System's membranes and bonds to dry, contaminant free surfaces. It has exceptional weather resistance, elongation and color stability.

Packaging:

Individually or 12 tubes per carton

Features:

- Paintable after skin forms
- Mold and Mildew resistance
- Substrate application range: 0°F to 125°F
- Cured sealant temperate range: -40°F to 300°F
- Cure rate: @ 75°F
 - Thin Skin: 24 Hours
 - Complete: 21 days

Color:

White, Tan, Gray, Red, Brown, Evergreen, Cool Sand, Clear and Black. Custom colors also available upon request.

Coverage:

15 linear feet per 10.3 oz. tube

Storage & Handling:

When Solar Seal 900 Caulking is stored indoors, out of direct sunlight, and in the original, unopened container at 75°F, the shelf life is 24 months. Always rotate stock.

Limitations:

- Substrate temperature is above 125°F
- Do not apply to a wet surface
- Intended for exterior use
- Not recommended for use of structural applications, joints under constant water submersion, or in contact with EPS



| Performance Specifications | |
|----------------------------|-----------------|
| VOC | 240 grams/Liter |
| Elongation | 200-400% |
| Sag | no sag |
| Hardness Shore A | 30 |
| Tack Free Time | 4 hours |