

IB Drain Liner / Metal Drop Scupper

Product Description:

IB Drain Liners are available in 2", 3" and 4" sizes. They are factory fabricated with round straight tube leaders and a reinforced IB PVC Single-Ply target flashing that allows for easy application through IB Galvanized Metal Drop Scuppers over installed IB field membranes. IB Drain Liners are ideal for use at ponding conditions at overhangs that will allow for the installation of a conductor head and down spout/drain line.

Packaging:

Individually or 25 per box.

Features:

- Factory fabricated flashing eliminates the errors of a field fabricated drain
- Easily attachable to the substrate
- Simple and easy to install from rooftop

Available Colors:

Available in all IB Membrane and DeckShield colors.

Product Description:

Galvanized Metal Drop Scuppers are designed for use with IB Drain Liners and are available all standard sizes.

Installation Instructions:

Install the new IB roof system field membrane and secure around drain opening in accordance with IB Specifications and Construction Details. Set Galvanized Metal Drop Scupper through opening and secure flange with a minimum of 4 fasteners. Secure and seal outer drain body to the structure or exterior wall and install conductor head and downspout (connection provided by others). Clean and prepare field membrane and drain liner target flashing seam areas. Hot air weld the perimeter of the target flashing to the field membrane with a minimum 1-1/2" weld to provide a watertight seal.



Membrane Drain Liner			
Type of Drain Liner	Base Target	Diameter	Tube Length
2" Drain Liner	12" x 12"	1-7/8"	12"
3" Drain Liner	12" x 12"	2-7/8"	12"
4" Drain Liner	12" x 12"	3-7/8"	12"
Galvanized Metal Drop Scupper			
2" Metal Drop	8" x 8"	1-7/8"	9-1/2"
3" Metal Drop	8" x 8"	2-7/8"	9-1/2"
4" Metal Drop	10" x 10"	3-7/8"	10"