Technical Data Sheet IB Dryer Vent / Exhaust Vent

Product Description:

The IB Dryer / Exhaust vent is a heavy-duty metal twopiece general purpose roof exhaust vent consisting of a Kynar 500® finished vent hood with internal backdraft dampers shipped with a ready to install galvanized flanged metal base. It is available to fit most common exhaust duct applications and is shipped with easily insertable insect resistant wire screens for non-dryer vent applications.

IB Roof Systems Dryer / Exhaust Vent comes equipped with an integral clamping band for easy, quick installation over factory fabricated IB PVC No-Cone Flashings. The vent hood can be removed as required for general maintenance or periodic cleaning.

Packaging:

One unit per box – includes vent hood, base and optional screens for non-dryer use application

Features:

- Built-in backdraft dampers close vent opening when not in use
- Heavy 24 gauge, G90 Galvanized metal construction
- Can be used for dryer, kitchen and bath exhaust vent applications
- Vent hood is stocked in White; or can be special ordered in Gray, Tan, Brown, Black or Galvanized finish color
- · 4" drop for easy connection to exhaust duct

Attachment:

Secure over installed IB roof membrane in accordance with IB Construction Details using IB SD#12, HD #14 or XHD #15 fasteners.

Approvals:

Complies with requirements of International Code Council (ICC) IRC 1502.3 and IMC 504.4





Product Data			Required IB Cone
Tube Diameter	Base Flange	Unit Weight	Flashing
4″	9″ x 9″	5 lbs.	4"No-Cone
6″	11″ x 11″	7 lbs.	6" No-Cone
8″	13″ x 13″	9 lbs.	8″ No-Cone

