

Product Description:

IB Pipe Flashings feature a factory fabricated, dielectrically welded reinforced IB PVC Single-Ply base and a 60 mil non-reinforced IB PVC Single-Ply upper. IB Pipe Flashings are designed for easy installation to reduce roof top labor and call backs by reducing workmanship errors. They are available in a variety of formats and sizes including Short A, size A-E pipe flashings in regular Cone, Oval 0.25 Cone, Round 0.25 Cone and custom No-Cone pipe flashings made to your specifications.

Short A and A-E cone flashings can easily be split and welded in the field as needed. See diagram below.



Packaging:

IB Pipe Flashings are shipped in cardboard boxes according to size.

Use:

IB Pipe Flashings are typically installed around roof top penetrations such as pipe, conduit, gas lines and other circular profile penetrations and flashings.

Available Colors:

Available in all standard IB membrane colors (White, Cool Sand, Cool Stone, Tan, Green, Red, Brown, and Gray). See color chart for representations.



IB Pipe Flashing Specifications					
Flashing Type	Base Flashing	Base	Top	Height	Box Quantity
Short A Cone	14"	3-1/4"	1/4"	5-1/2"	25
A Cone	15"	4-1/2"	1"	8-1/2"	25
B Cone	15-1/2"	5-1/4"	2-3/8"	10-1/2"	25
C Cone	17-1/2"	8"	4"	10-1/2"	10
D Cone	23"	12"	7-1/2"	9"	10
E Cone	28"	18"	9-1/2"	12"	10
4" Oval 0.25 Cone	22"	6"x10"	3"x6"	5"	25
4" Round 0.25 Cone	21"	-	-	5"	25
6" Round 0.25 Cone	24"	-	-	6"	25
8" Round 0.25 Cone	26"	-	-	6-1/2"	25

